




GL-A-MM13-3R0E

P.M. A.C. SERVO MOTOR



Motor model (2500-PPR/multi-turn absolute value/rotary transformer)	L(mm)		
	W/o brake	Permanent magnet brake	Electromagnetic brake
GL-A-MM13-3R0E-□-□A□	207	249	249

RATED POWER	3 Kw	STATOR RESISIANCE	NOT AVAILABLE
RATED VOLTS	380 V	STATOR REACTANCE	NOT AVAILABLE
MODE OF CONNECTION	Y	ROTOR RESISIANCE	NOT AVAILABLE
RATED FREQUENCY		ROTOR REACTANCE	NOT AVAILABLE
RATED CURRENT	7.8 A	EXCITATION REACTANCE	NOT AVAILABLE
RATED TORQUE	14.3 Nm	EXCITING REACTANCE	NOT AVAILABLE
REFERENCE SPEED	2000 r/min	INSULATION GRADE	F
MAX SPEED	3000 r/min	LEVEL OF PROTECTION	IP : 54
MOMENT OF INERTIA	18/19.9 kg/cm ²	SERIES	4 P
RATING		WEIGHT	10.8/112.5 Kg
COOLING FAN	RATED POWER RATED VOLTS		
ENCODER	IMPULSES PER MINUTE OUTPUT MODE		2500 TTL/HTL
BRAKE RIGGING	NAME THE DATA PARAMETER		ELECTROMAGNETIC